

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) A prosthetic foot for connecting to a leg portion having a support axis, the prosthetic foot comprising:
 - a. a lower member having anterior and posterior regions, a top and a bottom;
 - b. a post extending from the top of the lower member, the post fixedly connected to the lower member and positioned to be in substantial alignment with the support axis of the leg portion; and
 - c. an upper member having anterior and posterior regions and a ball joint positioned therein, the ball joint having an opening ~~for accepting in which the post is received therein; and~~
 - d. first and second separated buffers, the first buffer positioned between the lower member and the anterior region of the upper member and the second buffer positioned between the posterior regions of the lower member and the upper member.
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Currently Amended)The prosthetic foot of claim [[4]] 1, wherein the first and second buffers are formed of deformable material.
6. (Currently Amended)The prosthetic foot of claim [[4]] 1, wherein at least one of the first and second buffers includes a perforation extending therethrough.

7. (Original) The prosthetic foot of claim 6, wherein the perforation laterally extends through the first buffer.
8. (Currently Amended) The prosthetic foot of claim 7, wherein the first buffer includes a first lateral slit located at an anterior portion of the first buffer and extending through the anterior portion from an anterior end of the first buffer to the perforation.
9. (Original) The prosthetic foot of claim 8, wherein the anterior portion of the first buffer does not connect the upper member with the lower member.
10. (Original) The prosthetic foot of claim 6, wherein the perforation longitudinally extends through the first buffer.
11. (Original) The prosthetic foot of claim 6, wherein the perforation laterally extends through the second buffer.
12. (Withdrawn)
13. (Withdrawn)
14. (Currently Amended) The prosthetic foot of claim 6 further comprising a plug associated with the perforation, the plug configured for removable insertion into the perforation.
15. (Original) The prosthetic foot of claim 14, wherein the plug is of a material having a durometer different than a durometer of the buffer.
16. (Withdrawn)
17. (Currently Amended) The prosthetic foot of claim [[4]]_1, wherein at least one of the first and second buffers is connected to both of the upper and lower members.
18. (Currently Amended) The prosthetic foot of claim [[4]]_1, wherein at least one of the first and second buffers is connected to one of the lower and upper members.

19. (Currently Amended) The prosthetic foot of claim [[4]]1, wherein at least one of the first and second buffers is detachable.
20. (Withdrawn)
21. (Withdrawn)
22. (Withdrawn)
23. (Withdrawn)
24. (Withdrawn)
25. (Original) The prosthetic foot of claim 1, further comprising a heel member mounted on the bottom of the lower member.
26. (Original) The prosthetic foot of claim 25 further comprising a heel buffer positioned between the lower member and the heel member.
27. (Original) The prosthetic foot of claim 26, wherein the heel buffer does not fully occupy the space between the lower member and the heel member.
28. (Original) The prosthetic foot of claim 26, wherein the heel buffer does not extend anteriorly to the end of the heel member.
29. (Original) The prosthetic foot of claim 1, wherein the lower member includes top and bottom surfaces, and the top and bottom surfaces are generally curvilinear.
30. (Withdrawn)
31. (Withdrawn)
32. (Withdrawn)
33. (Withdrawn)

34. (Currently Amended) The prosthetic foot of claim [[3]] 1, further comprising a layer of material coated on a bottom surface of at least one of the first and second buffers and on a portion of a top surface of the lower member, wherein the material coated on the ~~bottom~~ top surface of the ~~buffer~~ lower member is same as material of the buffer.
35. (Currently Amended) A prosthetic foot for connecting to a leg portion having a support axis, the prosthetic foot comprising:
- e. a lower member having posterior and anterior regions;
 - f. an upper member having posterior and anterior regions;
 - g. a ball joint operably connected to the upper member;
 - h. a post fixedly connected to the lower member and positioned to be in substantial alignment with the support axis of the leg portion, the post connected to the ball joint;
 - i. a first resilient bumper positioned between the posterior region of the lower member and the posterior region of the upper member; and
 - j. a second resilient bumper separated from the first bumper and positioned between ~~the anterior region of the lower member and the anterior region of the upper member.~~
36. (Currently Amended) The prosthetic foot of claim 35, further comprising a heel member mounted on [[the]] a bottom of the lower member.
37. (Original) The prosthetic foot of claim 36 further comprising a heel buffer positioned between the lower member and the heel member.
38. (Original) The prosthetic foot of claim 36, wherein the heel buffer does not fully occupy the space between the lower member and the heel member.
39. (Currently Amended) The prosthetic foot of claim 37, wherein the heel buffer does not extend anteriorly to [[the]] an anterior end of the heel member.

40. (Currently Amended) A prosthetic foot for connecting to a leg portion having a support axis, the prosthetic foot comprising:

- k. a lower member;
- l. an upper member;
- m. a ball joint operably connected to the upper member;
- n. a post fixedly connected to the lower member and positioned to be in substantial alignment with the support axis of the leg portion, the post connected to the ball joint;
- o. a first resilient bumper positioned between the lower member and the upper member, anteriorly of the ball joint; and
- p. a second resilient bumper separated from the first bumper and positioned between the lower member and the upper member, posteriorly of the ball joint.

41. (Original) The prosthetic foot of claim 40, further comprising a heel member mounted on the bottom of the lower member.

42. (Original) The prosthetic foot of claim 41 further comprising a heel buffer positioned between the lower member and the heel member.

43. (Original) The prosthetic foot of claim 42, wherein the heel buffer does not fully occupy the space between the lower member and the heel member.

44. (Currently Amended) The prosthetic foot of claim 42, wherein the heel buffer does not extend anteriorly to [[the]] an anterior end of the heel member.

45. (Previously Presented) The prosthetic foot of claim 40, wherein the foot comprises only one ball joint and post combination.

46. (Previously Presented) The prosthetic foot of claim 35, wherein the foot comprises only one ball joint and post combination.

47. (Previously Presented) The prosthetic foot of claim 1, wherein the foot comprises only one ball joint and post combination.